



SDW2



Cold resistant & waterproof

TECHNICAL CHARACTERISTICS

Polyester knitted, 15 gauge
 Acrylic terry loop liner, 7 gauge
 2 layer coating :
 1st : Fully smooth latex coating
 2nd : Sandy latex palm and thumb coating
 Elastic wrist

SIZES : 8. 9. 10. 11.12

PACKAGING : Dozen | 120 pairs/ box

PERFORMANCE LEVELS

EN388 : 2242X						
ABRASION	0	1	2	3	4	
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	
PUNCTURE	0	1	2	3	4	
CUT TDM NEW EN388	A	B	C	D	E	F
IMPACT	No					

BENEFITS

- Cold resistant
- Waterproof
- Dexterity
- Good grip
- Flexibility
- Good fit
- Very comfortable

APPLICATIONS

- Exterior work extérieurs
- Refrigeration
- Precise operations
- Public Works
- Pulp and paper
- Mines
- Construction
- Transport

NORME EN 388
 Gloves giving protection from mechanical risks

The pictogram is accompanied by a 4-digit code, 4 or 5 being the best resistance rating.

a b c d

- a** Resistance to abrasion
Between 0 and 4 based on the number of cycles required to abrade through the sample glove (abrasion by sandpaper under a stipulated pressure).
- b** Blade cut resistance
Between 0 and 5, based on the number of cycles required to cut through the sample at a constant speed.
- c** Tear resistance
Between 0 and 4, based on the amount of force required to tear the sample.
- d** Puncture resistance
Between 0 and 4, based on the amount of force required to pierce the sample with a standard sized point.



x means that this performance is not tested.



Protection & performance
 bien en main!®

BCL GLOVE LTD
 21 Parc-Industriel, Saint-Pacôme
 (Quebec) Canada G0L 3X0
 T 418 852-2098 F 418 852-3330
info@akka.ca www.akka.ca