



CB-F-06



Chemical resistant & Food handling

TECHNICAL CHARACTERISTICS

Natural rubber fully dipped
 Palm reinforced with natural rubber and Chloroprene blend
 Thickness +/- 0.70 mm
 Total length 30 cm (12")
 Zig-Zag pattern provides a better grip while handling wet or dry areas

SIZES : 7. 8. 9. 10.

PACKAGING : Dozen | 120 pairs/ box

BENEFITS

- Resistance to broad spectrum of chemicals
- Soft flocklined absorbs perspiration and feels comfortable when exposed to solvents
- Excellent abrasion resistance 4/4

APPLICATIONS

- Janitorial
- Spray painting
- Leather processing
- Chemical cleaning
- Industrial cleaning
- Industrial laundry
- Decontamination works
- Sewage cleaning
- Pulp and paper

PERFORMANCE LEVELS

EN388 : 4121

ABRASION	0	1	2	3	4	
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	
PUNCTURE	0	1	2	3	4	
CUT TDM TEST NEW EN388	A	B	C	D	E	F
IMPACT	X			P		

NORME EN 388

Gloves giving protection from mechanical risks



a b c d


The pictogram is accompanied by a 4-digit code, 4 or 5 being the best resistance rating.

- a** Resistance to abrasion
Between 0 and 4 based on the number of cycles required to abrade through the sample glove (abrasion by sandpaper under a stipulated pressure).
- b** Blade cut resistance
Between 0 and 5, based on the number of cycles required to cut through the sample at a constant speed.
- c** Tear resistance
Between 0 and 4, based on the amount of force required to tear the sample.
- d** Puncture resistance
Between 0 and 4, based on the amount of force required to pierce the sample with a standard sized point.

X means that this performance is not tested.



BCL GLOVE LTD
 21 Parc-Industriel, Saint-Pacôme
 (Quebec) Canada G0L 3X0
 T 418 852-2098 F 418 852-3330
info@akka.ca www.akka.ca



STANDARD EN 374-1

General chemical protection




STANDARD EN 374-2

Gloves Giving Protection from Micro-Organisms

Niveau	AQL
1	4,0
2	1,5
3	0,65

The 'Micro-organism' pictogram is to be used when the glove conforms to at least a performance level 2 for the Penetration test. The penetration resistance is measured according to the ISO 2859 procedure which defines 3 levels of acceptable quality (AQL)



STANDARD EN 374-3

Gloves Giving Protection from Chemicals

Breakthrough time	Protection Index (class)
> 10 minutes	1
> 30 minutes	2
> 60 minutes	3
> 120 minutes	4
> 240 minutes	5
> 480 minutes	6

The 'Chemical resistant' glove pictogram must be accompanied by a 3-digit code. This code refers to the code letters of 3 chemicals (from a list of 18 standard defined chemicals), for which a breakthrough time of at least 30 minutes has been obtained.

- | | |
|-------------------------------|----------------------------|
| A Methanol | B Acetone |
| C Acetonitrile | D Dichloromethane |
| E Carbon disulfide | F Toluene |
| G Diethylamine | H Tetrahydrofuran |
| I Ethyl acetate | J n-Heptane |
| K Sodium hydroxide 40% | L Sulfuric acid 96% |

NEW MARKING

> 30 minutes for at least 6 chemicals tested	TYPE A JKLMNO
> 30 minutes for at least 3 chemicals tested	TYPE B JKL
> 30 minutes for at least 1 chemical tested	TYPE C

NEW MARKING

- | | |
|--------------------------------|--------------------------------|
| M Nitric acid 65% | N Acetic acid 99% |
| O Ammonia 25% | P Hydrogen peroxide 30% |
| S Hydrofluoric acid 40% | T Formaldehyde 37% |