



CONFORTGRIP / F



Cut resistance

TECHNICAL CHARACTERISTICS

Para-aramid knitted | Gauge 10
 Stitched reinforcement between thumb and forefinger
 Split leather palm with
 Seamless
 Elastic cuff

SIZES : 8. 9. 10. 11

PACKAGING : Dozen | 120 pairs/ box

BENEFITS

- Cut resistance ANSI A2 – 530 grams
- Cut resistance EN388 Level 3
- Excellent Abrasion resistance 4/4
- **Heat resistance**
- Very good resistance to puncture 4/4
- **Very good resistance to tear 4/4**

PERFORMANCE LEVELS

EN388 : 4344

ABRASION	0	1	2	3	4	
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	
PUNCTURE	0	1	2	3	4	
CUT TDM TEST NEW EN388	A	B	C	D	E	F
IMPACT	X			P		

ANSI CUT : A2

Number of grams : 530

A1	Light (200 – 499 g)
A2	Light to medium (500 – 999 g)
A3	Light to medium (1000 – 1499 g)
A4	Medium (1500 – 2199 g)
A5	Medium to heavy (2200 – 2999 g)
A6	High (3000 – 3999 g)
A7	High (4000 – 4999 g)
A8	High (5000 – 5999 g)
A9	High (6000 + g)

APPLICATIONS

- Automotive manufacturing
- Handling sharp-edged objects
- Scraps dealers
- Handling of cables
- Glass industry
- Plastic industry
- Rubber industry
- Machine shops



BCL GLOVE LTD
 21 Parc-Industriel, Saint-Pacôme
 (Quebec) Canada G0L 3X0
 T 418 852-2098 F 418 852-3330
info@akka.ca www.akka.ca



NORME EN 388

Gloves giving protection from mechanical risks

a b c d

The pictogram is accompanied by a 4-digit code, 4 or 5 being the best resistance rating.

- a** Resistance to abrasion
Between 0 and 4 based on the number of cycles required to abrade through the sample glove (abrasion by sandpaper under a stipulated pressure).
- b** Blade cut resistance
Between 0 and 5, based on the number of cycles required to cut through the sample at a constant speed.
- c** Tear resistance
Between 0 and 4, based on the amount of force required to tear the sample.
- d** Puncture resistance
Between 0 and 4, based on the amount of force required to pierce the sample with a standard sized point.

x means that this performance is not tested.



GUIDE TO THE NEW CUT LEVELS ANSI & EN388



200 - 499 grams
LIGHT cut hazards
Wood / paper, warehouse, General carpentry, construction, general purpose small parts assembly



500 - 999 grams
LIGHT/MEDIUM cut hazards
Wood / paper, warehouse, General carpentry, small parts assembly, general purpose, construction



1000 - 1499 grams
LIGHT/MEDIUM cut hazards
Wood / paper, warehouse, General carpentry, small parts assembly, general purpose, construction



1500 - 2199 grams
MEDIUM cut hazards
Aerospace, automotive, general carpentry, glass, sheet metal users /window glazers, wood / paper, metal fabrication, metalworking, plastic, plumbers, appliance manufacturing



2200 - 2999 grams
MEDIUM/HEAVY cut hazards
Aerospace, glass, sheet metal users /window glazers, wood / paper, metal, fabrication, metalworking, plastic, plumbers, appliance manufacturing, automotive, general carpentry



3000 - 3999 grams
HIGH cut hazards
Aerospace, appliance manufacturing, automotive, general carpentry, glass, sheet metal users /window glazers, wood / paper, metal fabrication, metalworking, plastic, plumbers



4000 - 4999 grams
HIGH cut hazards
Aerospace, metal stamping, metal recycling, metal fabrication / metal working, appliance manufacturing, automotive, general carpentry, glass, sheet metal users /window glazers, wood / paper, metal fabrication, Plumbers metalworking, plastic



5000 - 5999 grams
HIGH cut hazards
Aerospace, metal stamping, metal recycling, metal fabrication /metal working, appliance manufacturing, automotive, general carpentry, glass, sheet metal users /window glazers, wood / paper, metal fabrication, metalworking, plastic, plumbers



6000 + grams
HIGH cut hazards
Aerospace, metal stamping, metal recycling, metal fabrication / metal working, appliance manufacturing, automotive, general carpentry, glass, sheet metal users /window glazers, wood / paper, metal fabrication, Plumbers, metalworking, plastic

* Grams : Degree of cut resistance