

EXTRAFIT



4242

General works

TECHNICAL CHARACTERISTICS

100 % Polyamide with elasthane | Gauge 10
CLEAN PU coated palm and fingers
 Seamless
 Elastic wrist

SIZES : 6. 7. 8. 9. 10. 11. 12

PACKAGING : By ten | 200 pairs/ box

BENEFITS

- Very good resistance to abrasion 4/4
- Very good resistance to tear 4/4
- Cut resistant Level A1 (ANSI) and Level 2 (EN388)
- Non-toxic
- Durability

APPLICATIONS

- General handling
- General mechanics
- Construction
- Warehousing

PERFORMANCE LEVELS

EN388 : 4242

ABRASION	0	1	2	3	4	
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	
PUNCTURE	0	1	2	3	4	
CUT TDM TEST NEW EN388	A	B	C	D	E	F
IMPACT	X			P		

NORME EN 388

Gloves giving protection from mechanical risks

a b c d

The pictogram is accompanied by a 4-digit code, 4 or 5 being the best resistance rating.

- a** Resistance to abrasion
Between 0 and 4 based on the number of cycles required to abrade through the sample glove (abrasion by sandpaper under a stipulated pressure).
- b** Blade cut resistance
Between 0 and 5, based on the number of cycles required to cut through the sample at a constant speed.
- c** Tear resistance
Between 0 and 4, based on the amount of force required to tear the sample.
- d** Puncture resistance
Between 0 and 4, based on the amount of force required to pierce the sample with a standard sized point.

X means that this performance is not tested.



BCL GLOVE LTD
 21 Parc-Industriel, Saint-Pacôme
 (Quebec) Canada G0L 3X0
 T 418 852-2098 F 418 852-3330
info@akka.ca www.akka.ca



GUIDE TO THE NEW CUT LEVELS

ANSI & EN388

ANSI CUT

A1

200 - 499 grams

LIGHT cut hazards

Wood / paper, warehouse, General carpentry, construction, general purpose small parts assembly

ANSI CUT

A2

500 - 999 grams

LIGHT/MEDIUM cut hazards

Wood / paper, warehouse, General carpentry, small parts assembly, general purpose, construction

ANSI CUT

A3

1000 - 1499 grams

LIGHT/MEDIUM cut hazards

Wood / paper, warehouse, General carpentry, small parts assembly, general purpose, construction

ANSI CUT

A4

1500 - 2199 grams

MEDIUM cut hazards

Aerospace, automotive, general carpentry, glass, sheet metal users /window glazers, wood / paper, metal fabrication, metalworking, plastic, plumbers, appliance manufacturing

ANSI CUT

A5

2200 - 2999 grams

MEDIUM/HEAVY cut hazards

Aerospace, glass, sheet metal users /window glazers, wood / paper, metal, fabrication, metalworking, plastic, plumbers, appliance manufacturing, automotive, general carpentry

ANSI CUT

A6

3000 - 3999 grams

HIGH cut hazards

Aerospace, appliance manufacturing, automotive, general carpentry, glass, sheet metal users /window glazers, wood / paper, metal fabrication, metalworking, plastic, plumbers

ANSI CUT

A7

4000 - 4999 grams

HIGH cut hazards

Aerospace, metal stamping, metal recycling, metal fabrication / metal working, appliance manufacturing, automotive, general carpentry, glass, sheet metal users /window glazers, wood / paper, metal fabrication, Plumbers metalworking, plastic

ANSI CUT

A8

5000 - 5999 grams

HIGH cut hazards

Aerospace, metal stamping, metal recycling, metal fabrication /metal working, appliance manufacturing, automotive, general carpentry, glass, sheet metal users /window glazers, wood / paper, metal fabrication, metalworking, plastic, plumbers

ANSI CUT

A9

6000 + grams

HIGH cut hazards

Aerospace, metal stamping, metal recycling, metal fabrication / metal working, appliance manufacturing, automotive, general carpentry, glass, sheet metal users /window glazers, wood / paper, metal fabrication, Plumbers, metalworking, plastic

* Grams :
Degree of cut resistance