


Summitech











TECHNICAL CHARACTERISTICS

Kevlar glove | Gauge 10 Latex coated palm and fingers Elastic cuff

> SIZES: 7. 8. 9. 10. 11.

PACKAGING: Dozen | 120 pairs/box

BENEFITS

- Cut resistance EN388 Level 3
- Very good resistance to perforation 4/4
- Good abrasion resistance 3/4
- Heat resistant 250° C (482 ºF)
- Good dexterity and comfortable

PERFORMANCE LEVELS

EN388: 3344						
ABRASION	0	1	2	3	4	
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	
PUNCTURE	0	1	2	3	4	
CUT TDM TEST NEW EN388	Α	В	С	D	Е	F
IMPACT	X			Р		

ANSI CUT: A2			
Number of grams : 500			
A1	Light (200 – 499 g)		
<u>A2</u>	Light to medium (500 – 999 g)		
A3	Light to medium (1000 – 1499 g)		
A4	Medium (1500 – 2199 g)		
A5	Medium to heavy (2200 – 2999 g)		
A6	High (3000 – 3999 g)		
A7	High (4000 – 4999 g)		
A8	High (5000 – 5999 g)		
A9	High (6000 + g)		

APPLICATIONS

- Handling sharp-edged objects
- Recycling and garbage collection
- Press and stamping
- Engineering
- Automotive industry
- Paper and cardboard industries
- Metallurgical industry







BCL GLOVE LTD 21 Parc-Industriel, Saint-Pacôme (Quebec) Canada GOL 3X0 T 418 852-2098 F 418 852-3330 info@akka.ca www.akka.ca




NORME EN 388

Gloves giving protection from mechanical risks

abcd -

The pictogram is accompanied by a 4-digit code, 4 or 5 being the best resistance rating.



- Blade cut resistance

 Between 0 and 5, based on the number of cycles required to cut through
 the sample at a constant speed.
- C Tear resistance Between 0 and 4, based on the amount of force required to tear the sample.
- Puncture resistance

 Between 0 and 4, based on the amount of force required to pierce
 the sample with a standard sized point.

means that this performance is not tested.





GUIDE TO THE NEW CUT LEVELS

ANSI & EN388



200 - 499 grams LIGHT cut hazards

Wood / paper, warehouse, General carpentry, construction, general purpose small parts assembly



500 - 999 grams LIGHT/MEDIUM cut hazards

Wood / paper, warehouse, General carpentry, small parts assembly, general purpose, construction



1000 - 1499 grams LIGHT/MEDIUM cut hazards

Wood / paper, warehouse, General carpentry, small parts assembly, general purpose, construction



1500 - 2199 grams

MEDIUM cut hazards

Aerospace, automotive, general carpentry, glass, sheet metal users /window glazers, wood / paper, metal fabrication, metalworking, plastic, plumbers, appliance manufacturing



2200 - 2999 grams

MEDIUM/HEAVY cut hazards

Aerospace, glass, sheet metal users /window glazers, wood / paper, metal, fabrication, metalworking, plastic, plumbers, appliance manufacturing, automotive, general carpentry



3000 - 3999 grams HIGH cut hazards

Aerospace, appliance manufacturing, automotive, general carpentry, glass, sheet metal users /window glazers, wood / paper, metal fabrication, metalworking, plastic, plumbers



4000 - 4999 grams HIGH cut hazards

Aerospace, metal stamping, metal recycling, metal fabrication / metal working, appliance manufacturing, automotive, general carpentry, glass, sheet metal users /window glazers, wood / paper, metal fabrication, Plumbers metalworking, plastic ANSI CUT

5000 - 5999 grams HIGH cut hazards

Aerospace, metal stamping, metal recycling, metal fabrication /metal working, appliance manufacturing, automotive, general carpentry, glass, sheet metal users /window glazers, wood / paper, metal fabrication, metalworking, plastic, plumbers



6000 + grams HIGH cut hazards

Aerospace, metal stamping, metal recycling, metal fabrication / metal working, appliance manufacturing, automotive, general carpentry, glass, sheet metal users /window glazers, wood / paper, metal fabrication, Plumbers, metalworking, plastic

* Grams :

Degree of cut resistance

CHOOSING

ANSI LEVELS

