



S003

Fine Handling



TECHNICAL CHARACTERISTICS

Polyester liner | Gauge 13
 Nitrile rubber coated palm and fingers
 Elastic wrist
 Seamless

SIZES : 7. 8. 9. 10. 11

PACKAGING : Dozen | 144 pairs/ box

BENEFITS

- Extremely resistant to abrasion EN388 4/ 4 | ANSI 6
- **Perfect dexterity**
- Hypoallergenic
- Very comfortable
- Light and breathes

APPLICATIONS

- General handling
- Mechanical
- Construction
- Warehousing
- Cabling

PERFORMANCE LEVELS

EN388 : 4121						
ABRASION	0	1	2	3	4	
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	
PUNCTURE	0	1	2	3	4	
CUT TDM TEST NEW EN388	A	B	C	D	E	F
IMPACT	X			P		



NORME EN 388
 Gloves giving protection
 from mechanical risks

a b c d

The pictogram is accompanied by a 4-digit code,
 4 or 5 being the best resistance rating.

- a** Resistance to abrasion
 Between 0 and 4 based on the number of cycles required to abrade through the sample glove (abrasion by sandpaper under a stipulated pressure).
- b** Blade cut resistance
 Between 0 and 5, based on the number of cycles required to cut through the sample at a constant speed.
- c** Tear resistance
 Between 0 and 4, based on the amount of force required to tear the sample.
- d** Puncture resistance
 Between 0 and 4, based on the amount of force required to pierce the sample with a standard sized point.

X means that this performance is not tested.



BCL GLOVE LTD
 21 Parc-Industriel, Saint-Pacôme
 (Québec) Canada G0L 3X0
 T 418 852-2098 F 418 852-3330
info@akka.ca www.akka.ca