



S018

Chemical resistant & Food handling

TECHNICAL CHARACTERISTICS

- PVC. Double thickness
- Cotton jersey lining
- Palm rough finish
- Total length 35 cm (14")

SIZES : 10.

PACKAGING : Dozen | 72 pairs/ box

BENEFITS

- Excellent abrasion resistance 4/4
- Good grip
- Chemical resistant

APPLICATIONS

- Chemical processing
- Oil and gas industries
- Public and general works
- Cleaning and handling of greasy parts
- Fisheries

PERFORMANCE LEVELS

EN388 : 4121

| | | | | | | |
|---------------------------|----------|----------|----------|---|----------|---|
| ABRASION | 0 | 1 | 2 | 3 | 4 | |
| CUT | 0 | 1 | 2 | 3 | 4 | 5 |
| TEAR | 0 | 1 | 2 | 3 | 4 | |
| PUNCTURE | 0 | 1 | 2 | 3 | 4 | |
| CUT TDM TEST NEW EN388 | A | B | C | D | E | F |
| IMPACT | X | | | P | | |

NORME EN 388

Gloves giving protection from mechanical risks

a b c d

The pictogram is accompanied by a 4-digit code, 4 or 5 being the best resistance rating.

- a** Resistance to abrasion
Between 0 and 4 based on the number of cycles required to abrade through the sample glove (abrasion by sandpaper under a stipulated pressure).
- b** Blade cut resistance
Between 0 and 5, based on the number of cycles required to cut through the sample at a constant speed.
- c** Tear resistance
Between 0 and 4, based on the amount of force required to tear the sample.
- d** Puncture resistance
Between 0 and 4, based on the amount of force required to pierce the sample with a standard sized point.

X means that this performance is not tested.



BCL GLOVE LTD
 21 Parc-Industriel, Saint-Pacôme
 (Quebec) Canada G0L 3X0
 T 418 852-2098 F 418 852-3330
info@akka.ca www.akka.ca