



SDA9



Superior cut resistance

TECHNICAL CHARACTERISTICS

HPPE, glassfiber and polyester.
 Reinforcement between thumb and forefinger.
 Gauge 13.
 Black Nitrile coated palm and fingers, sandy finished.
 Elastic wrist.

SIZES : 9. 10. 11

PACKAGING : Dozen | 120 pairs/ box

BENEFITS

- Superior Cut resistance ANSI Level 9 and EN388 Level F
- Excellent abrasion resistance 4/4
- Dexterity
- Durability
- Flexibility and comfort

APPLICATIONS

- Handling sharp-edged objects
- Aerospace
- Automotive manufacturing
- Construction
- Metal fabrication
- Plastic injection molding

EN388 : 4X43F

ABRASION	0	1	2	3	4	
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	
PUNCTURE	0	1	2	3	4	
CUT TDM TEST NEW EN388	A	B	C	D	E	F
IMPACT	No					

ANSI CUT : A9

A1	Light (200 – 499 g)
A2	Light to medium (500 – 999 g)
A3	Light to medium (1000 – 1499 g)
A4	Medium (1500 – 2199 g)
A5	Medium to heavy (2200 – 2999 g)
A6	High (3000 – 3999 g)
A7	High (4000 – 4999 g)
A8	High (5000 – 5999 g)
A9	High (6000 + g)



BCL GLOVE LTD
 21 Parc-Industriel, Saint-Pacôme
 (Quebec) Canada G0L 3X0
 T 418 852-2098 F 418 852-3330
info@akka.ca www.akka.ca



GUIDE TO THE NEW CUT LEVELS

ANSI & EN388



200 - 499 grams
LIGHT cut hazards
Wood / paper, warehouse,
General carpentry,
construction, general purpose
small parts assembly



1500 - 2199 grams
MEDIUM cut hazards
Aerospace, automotive,
general carpentry, glass, sheet
metal users /window glazers,
wood / paper, metal
fabrication, metalworking,
plastic, plumbers, appliance
manufacturing



4000 - 4999 grams
HIGH cut hazards
Aerospace, metal stamping,
metal recycling, metal
fabrication / metal working,
appliance manufacturing,
automotive, general carpentry,
glass, sheet metal users
/window glazers, wood / paper,
metal fabrication, Plumbers
metalworking, plastic

* Grams :
Degree of cut resistance




500 - 999 grams
LIGHT/MEDIUM cut hazards
Wood / paper, warehouse,
General carpentry, small parts
assembly, general purpose,
construction



2200 - 2999 grams
MEDIUM/HEAVY cut hazards
Aerospace, glass, sheet metal
users /window glazers, wood /
paper, metal, fabrication,
metalworking, plastic, plumbers,
appliance manufacturing,
automotive, general carpentry



5000 - 5999 grams
HIGH cut hazards
Aerospace, metal stamping,
metal recycling, metal
fabrication /metal working,
appliance manufacturing,
automotive, general carpentry,
glass, sheet metal users
/window glazers, wood / paper,
metal fabrication, metalworking,
plastic, plumbers



1000 - 1499 grams
LIGHT/MEDIUM cut hazards
Wood / paper, warehouse,
General carpentry, small parts
assembly, general purpose,
construction



3000 - 3999 grams
HIGH cut hazards
Aerospace, appliance
manufacturing, automotive,
general carpentry, glass, sheet
metal users /window glazers,
wood / paper, metal
fabrication, metalworking,
plastic, plumbers



6000 + grams
HIGH cut hazards
Aerospace, metal stamping,
metal recycling, metal
fabrication / metal working,
appliance manufacturing,
automotive, general carpentry,
glass, sheet metal users
/window glazers, wood / paper,
metal fabrication, Plumbers,
metalworking, plastic