



Protection & performance
well in hand!®

CUT PROTECTION GLOVE WITH ESD & TACTILE FUNCTION

G18N7SD

SIZES : 7 ○ 8 ○ 9 ○ 10 ○ 11 ○ 12 ○

PACK OF 12 PAIRS



**Touch
Screen Glove**

DESCRIPTION :

18 Gages HPPE, carbon, steel and polyester knit.

Micro foam nitrile coating with thumb crotch reinforcement.

- Super lightweight
- Excellent fit, dexterity and grip
- Durable (ABRASION ANSI 5)
- Ultra thin and excellent sensitivity in cut protection level ANSI CUT A7
- Oil, water and grease repellency

APPLICATIONS :

Aerospace, metal stamping, metal recycling, metal fabrication / metal working, appliance manufacturing, automotive, general carpentry ...

EN 16350



ESD

16350 STANDARD

RESISTANCE TO ELECTROSTATIC PROPERTIES

This test indicates that the glove is antistatic: the glove cannot be loaded with electricity statically. The glove is subject to the test method in EN 1149-2.

This test is to measure its vertical resistance in Ohms.

EN 388



4X42F

EN 388 STANDARD - Mechanical risks



4/4 : Abrasion resistance

X/4 : Cut resistance **F**, see new test below

4/4 : Tear resistance

2/4 : Puncture resistance

F : Cut resistance ISO 13997

ANSI



ABRASION

ABRASION ANSI 5 offer a superior durability.

Level 5/6 mean the glove can resist till more than 10 000 cycles of 180 grits abrasive material before perforated the glove.

ANSI CUT



ANSI CUT 7 resist from 4000 to 4999 grams of weight from a blade in mouvement.

HEAVY cut hazards

EN 407



X1XXXX

Resistance to contact heat

The glove can be expose to a temperature of 100°C for at least 15 seconds of manipulation.



BCL GLOVE LTD

21 Parc-Industriel, Saint-Pacôme, (Québec) Canada, G0L 3X0

T 418 852-2098 F 418 852-3330

INFO@AKKA.CA

WWW.AKKA.CA