



# # PL6BK



Fine handling

## TECHNICAL CHARACTERISTICS

Nylon glove | Gauge 13  
 PU coated palm and fingers  
 Seamless  
 Elastic wrist

SIZES : 7. 8. 9. 10. 11

PACKAGING : Dozen | 120 pairs/ box

## BENEFITS

- Very good resistance to abrasion 4/4
- Resistant to oil
- Great comfort
- Durability
- Dexterity
- Light and breathes

## APPLICATIONS

- Sorting small parts and precision assembly
- General mechanics
- Assembly of electronic components
- Finishing works
- Packaging
- Agriculture

## PERFORMANCE LEVELS

### EN388 : 4131

ABRASION	0	1	2	3	<b>4</b>	
CUT	0	<b>1</b>	2	3	4	5
TEAR	0	1	2	<b>3</b>	4	
PUNCTURE	0	<b>1</b>	2	3	4	
CUT TDM TEST NEW EN388	A	B	C	D	E	F
IMPACT	X			P		



### NORME EN 388

Gloves giving protection from mechanical risks

a b c d

The pictogram is accompanied by a 4-digit code, 4 or 5 being the best resistance rating.

- a** Resistance to abrasion  
Between 0 and 4 based on the number of cycles required to abrade through the sample glove (abrasion by sandpaper under a stipulated pressure).
- b** Blade cut resistance  
Between 0 and 5, based on the number of cycles required to cut through the sample at a constant speed.
- c** Tear resistance  
Between 0 and 4, based on the amount of force required to tear the sample.
- d** Puncture resistance  
Between 0 and 4, based on the amount of force required to pierce the sample with a standard sized point.



BCL GLOVE LTD  
 21 Parc-Industriel, Saint-Pacôme  
 (Quebec) Canada G0L 3X0  
 T 418 852-2098 F 418 852-3330  
[info@akka.ca](mailto:info@akka.ca) [www.akka.ca](http://www.akka.ca)