

ANSI CUT LEVEL



200 - 499 grams
BASIC :
Cut Hazard
Wood / paper, warehouse,
General carpentry,
construction, general purpose
small parts assembly



500 - 999 grams
BASIC :
Cut Hazard
Wood / paper, warehouse,
General carpentry, small parts
assembly, general purpose,
construction



1000 - 1499 grams
INTERMEDIATE:
Cut Hazard
Wood / paper,
warehouse, General
carpentry, small parts
assembly, general purpose,
construction



1500 - 2199 grams
INTERMEDIATE:
Cut Hazard
Aerospace, automotive,
general carpentry, glass,
sheet metal users /window
glazers, wood / paper, metal
fabrication, metalworking,
plastic, plumbers, appliance
manufacturing



2200 - 2999 grams
HIGH : Cut Hazard
Aerospace, glass, sheet metal
users /window glazers, wood
/paper, metal, fabrication,
metalworking, plastic,
plumbers, appliance
manufacturing, automotive,
general carpentry



3000 - 3999 grams
HIGH : Cut Hazard
Aerospace, appliance
manufacturing, automotive,
general carpentry, glass, sheet
metal users /window glazers,
wood / paper, metal
fabrication, metalworking,
plastic, plumbers



4000 - 4999 grams
SUPERIOR :
Cut Hazard
Aerospace, metal stamping,
metal recycling, metal
fabrication, appliance
manufacturing, automotive,
general carpentry, glass,
sheet metal users /window
glazers, wood / paper,
fabrication, Plumbers



5000 - 5999 grams
SUPERIOR :
Cut Hazard
Aerospace, metal stamping,
metal recycling, metal
fabrication, appliance
manufacturing, automotive,
general carpentry, glass, sheet
metal users /window glazers,
wood / paper, plastic, plumbers



6000 + grams
SUPERIOR :
Cut Hazard
Aerospace, metal stamping,
metal recycling, metal
fabrication, appliance
manufacturing, automotive,
general carpentry, glass, sheet
metal users /window glazers,
wood / paper, Plumbers, plastic

* Grams :
Degree of cut resistance



Protection & performance
well in hand!®